



ET&F[®] MODEL 710

- Engineered for the power and durability required for use with steel and concrete substrates
- Power to drive into poured concrete or 10ga
- Capable of driving pins 1-1/8" to 3 - 1/2" long
- Smooth and knurled collated pins available and special SCRAIL[®] STEELTHREAD STRUCTURAL
- Systems approach with tools and fasteners provides single source responsibility



CONTACT & SERVICE

Our sales team
is available at:

P +1 800 2482376

F +1 440 2480423

E etf@beck-fastening.com

www.beck-fastening.com

PIN TYPE

ASM-144 PINS, ASM-120 PINS, AKN-144 PINS, SCRAIL[®] STEELTHREAD STRUCTURAL

ET&F® Model 710

TOOL CHARACTERISTICS

Height	Width	Length	Weight
15 1/2 inch	5.60 inch	14.53 inch	8.7 lbs
387 mm	142 mm	369 mm	3.59 kg

Pressure 70 - 120 psi | 5 - 8 bar

Lubricant Non-detergent pneumatic tool lubricant

Recommended steel thickness

20 ga - 10 ga



Model ET&F 710

FASTENER DATA

Pin Type	ASM-120 PINS, ASM-144 PINS, AKN-144 PINS, SCRAIL® STEELTHREAD STRUCTURAL	ASM-120 PINS, ASM-144 PINS, AKN-144 PINS
Wire	0.100" - 0.150" 2.5 - 3.8 mm	
Shank	Smooth, Knurled, SCRAIL® STEELTHREAD STRUCTURAL	
Head	5.5 – 7.1 mm 0.216" – 0.279"	
Length	1 1/8 - 3 1/2" 28 mm - 90 mm	
Coating	Electro Galvanized	Mechanically Galvanized
Magazine Capacity	200 - 300 pins/SCRAIL®	

ACTUATION & LOADING

Actuation System:

Full sequential actuation

Loading:

Coil

APPLICATIONS

- Wood sheathing and wood structural panel diaphragms to steel framing (IAPMO ES ER-335)
- Hardie Plank® lap siding to CMU (ICC-ER-2290)
- Wood nailers to steel, concrete, cmu and trailer construction, basement waterproofing