



F48AC CN15W-57A



TOOL FEATURES

- Powerful Wire Coil Nailer for nails up to 57 mm (2 1/4")
- Patent pending design with good ergonomics and excellent tool balance
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue

15° WIRE COIL NAILS

- Can be provided in standard steel or stainless steel A2 or A4
- Available as bright, electro-galvanized, hot-dipped or coppered version
- Can be delivered in smooth, ring, screw or knurled version



CONTACT & SERVICE

Our sales team
is available at:

P +39 051 6018226
fasco@fasco-tools.com
www.fasco-tools.com

DESCRIPTION

- High impact engineered plastic magazine with adjustable bottom steel plate
- Contact "Bump" fire trigger for industrial applications
- Side protectors safeguard tool from contact with rough surfaces

APPLICATIONS

- Garden furniture
- Sheathing
- Fencing
- Pallets
- Boxes and crates
- Cable reels

HANDLING

1. Load the coil in the magazine
2. Position first nail in nose channel and align top of nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
290 mm	130 mm
11.41 inch	5.12 inch
Length	Weight
290 mm	2,85 kg
11.41 inch	6.28 lbs

Pressure

5 - 7 bar | 70 - 100 psi

Air consumption per shot

1.46 L. | 0.052 SCF
Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Diameter	2.10 - 2.50 mm 0.083 - 0.099"
Length	25 - 57 mm 1 - 2 ¼"
Head	4.8 - 6.2 mm 0.189 - 0.245"
Collation Type	15° Wire Coil Nails
Capacity	200 / 300

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 94.04 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 88.06 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

2.81 m/s²

ACTUATION & LOADING

Actuation System: Contact
Actuation
Loading: Coil

VARIATIONS

- F58A CN15W-70
for nails up to 70 mm (2 ¾")
- F58AC CN15W-80
for nails up to 80 mm (3 ¼")

