



F58AC CN15W-80



TOOL FEATURES

- Powerful Wire Coil Nailer for Nails up to 80 mm (3 1/4")
- Patent pending design with good ergonomics and excellent tool balance
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue

15° WIRE COIL NAILS

- Can be provided in standard steel or stainless steel A2 or A4
- Available as bright, electro-galvanized, hot-dipped or coppered version
- Can be delivered in smooth, ring, screw or knurled version



CONTACT & SERVICE

**Our sales team
is available at:**

P +39 051 6018226
fasco@fasco-tools.com
www.fasco-tools.com

DESCRIPTION

- High impact engineered plastic magazine with adjustable bottom steel plate
- Body in high strength magnesium
- Magazine with adjustable bottom steel plate

APPLICATIONS

- Pallets
- Boxes & crates
- Cable reels
- Roof joists
- Rafters & joists
- Trusses
- Decking
- Siding
- Fencing
- Garden furniture

HANDLING

1. Load the coil in the magazine
2. Position first nail in nose channel and align top of nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry and dirty tool by cleaning and lubricating regularly

TOOL CHARACTERISTICS

Height	Width
365 mm	130 mm
14.37 inch	5.12 inch
Length	Weight
310 mm	3.85 kg
12.20 inch	8.48 lbs

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

1.86 L. | 0.066 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Diameter	2.50 - 3.30 mm 0.098 - 0.130"
Length	50 - 83 mm 2 - 3 1/4"
Head	7 mm 0.275"
Pitch	8 mm 0.315"
Nail Type	15° Drahtcoil Nägel
Capacity	200 300

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 101.00 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 94.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.63 m/s²

ACTUATION & LOADING

Actuation System:

Contact actuation

Loading: Coil

VARIATIONS

- F58A CN15W-70
for nails up to 70 mm (2 3/4")
- F48AC CN15W-57A
for nails up to 57 mm (2 1/4")

