



## F70G FENCE 45-315

TRANSITION PERIOD: Product branding changes according to the new brand design.

### TOOL- FEATURES

- Powerful cordless tool to countersink 45 mm (1 3/4") FENCE staples in pressure treated lumber
- Good balance, reduced weight
- Tool-free depth of drive adjustment
- Special nose for fence application

### FENCE STAPLES

- Patented Diamond Coating and precision divergent points for superior holding power compared to manual installation
- Hot dipped galvanized wire with minimum 350 g/m<sup>2</sup> (50 µm) zinc layer (Class 4) for maximum staple life



### CONTACT & SERVICE

Our sales team  
is available at:

P +43 7724 2111-671  
sales@beck-fastening.com  
www.beck-fastening.com

### DESCRIPTION

The two divergent points and the patented Diamond Coating ensure an excellent holding power compared to manual installation.



**DIAMOND  
COATING**  
Highly Adhesive

**PRECISION  
DIVERGENT  
POINTS**



## APPLICATIONS

- Fencing: batten fencing, electrified single wire, snow control fencing and light mesh fencing
- Pet enclosures, poultry fencing
- Coaxial and fiber optic utility wire applications

## HANDLING

1. Load fuel cell
2. Load fastener from the top into the magazine
3. Connect battery
4. Clean and maintain gas tool regularly

## TOOL CHARACTERISTICS

Height	Width
373 mm	108 mm
14.70 inch	4.25 inch
Length	Weight
351 mm	3,74 kg
13.82 inch	8.24 lbs

### Shot limit

1000 Shots / Hour

### Speed

2-3 Shots / Second

**Gas type** Liquid petroleum gas

### Operating temperature

-7 / 49° C | 19 / 120° F

## FASTENER DATA

	FENCE staples
<b>Diameter</b>	2,70 - 3,30 mm 0.106 - 0.130"
<b>Outside Crown</b>	12,80 mm   0.503"
<b>Inside Crown</b>	6,70 mm   0.264"
<b>Length</b>	25 - 45 mm 1 - 1 3/4"
<b>Capacity</b>	75
<b>Staple Type</b>	F45-315 FENCE staples

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 97.20 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 100.20 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

5.26 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System:

Full Sequential Actuation

Loading: Top Loading

## VARIATIONS

- F46A FENCE 45-315  
Pneumatic FENCE Stapler

## FASTENER PACKAGING:

Dimensions (WxHxD):

5.590x3.397x8.976"

Weight: 15.10 lbs (6,85 kg)

Quantity: 1500 pieces per pack

## BATTERY

### Input Charge

220-240 VAC 50 Hz

### Charge Time

2 hours

### Capacity

1650 MaH

### Voltage

6 VDC

### Shots / Battery

Max. 5200

### Shots / Fuel Cell

Max. 1200