

LIGNOLOC® WITH STEPPED SHAFT

The new LIGNOLOC® with a diameter of 3.5 mm and a length range of 22-40 mm is ideal for filigree precision work, particularly in kitchen or furniture construction, as well as for fine work in interior fittings or interior wall paneling. The nail with head impresses with its stepped shaft, which minimizes wood splitting, making it a perfect choice for carpenters and joiners.

LIGNOLOC® WOODEN NAILS

- Sustainable and circular
- No wood glue necessary
- Much faster than screws
- Made of local beech wood
- Fungus-resistant
- No corrosion and streaking on wood



CONTACT & SERVICE

Our sales team is available at:

P +43 7724 2111-671 sales.int@beck-fastening.com www.beck-fastening.com

DESCRIPTION

LIGNOLOC® is the world's first shootable wooden nail, perfect for ecological and circular timber construction and ecological wood processing.

The revolutionary LIGNOLOC® wooden nails are made from indigenous beech wood. Their mechanical properties allow the nails to be driven into solid structural timber* and wooden materials with the FASCO® LIGNOLOC® pneumatic nailer, without predrilling, to form an inseparable bond with the timber.

* for wood weighing 350 to 500 kg/m³ and in compliance with edge distances specified in Eurocode 5



RAIMUND BECK NAGELTECHNIK GmbH Raimund-Beck-Straße 1 | 5270 Mauerkirchen

P +43 7724 2111-0 | F +43 7724 2111-20 E sales.int@beck-fastening.com W www.beck-fastening.com Follow us







LIGNOLOC® WOODEN NAILS WITH STEPPED SHAFT



FASTENER DATA

	LIGNOLOC®
	wooden nails
Diameter	3.5 mm 0.138"
Length	22 – 40 mm
	7/8 – 1 9/16"
Head	4.2 mm 0.165"
Material	compressed
	beech wood
Color	natural
Capacity	150
Collation	15° Plastic Sheet
Туре	recyclable

COMPATIBLE TOOLS

F33 CN15-PS40 LIGNOLOC®

APPLICATION

- Coffins
- Furniture interior / exterior
- Trim works
- Kitchen units
- Interior cladding
- Prefixation
- Set construction



